

THE **6**
PASSIVE
WEDGE 30



Speaker type	6.5" time coherent point-source coaxial
Passive Active	Passive
Enclosure type	Vented
SPL	Measurement data 111 dB cont. / 122 dB peak
Frequency Range	Measurement data 100 Hz - 20 kHz
Sensitivity	93 dB / 1W/m
Power handling	200 W
Impedance	8 Ω
Woofer	6.5" woofer
Tweeter Hochtöner	1" soft dome
Directivity horizontal x vertical in Deg°	85° x 85°
Input Terminal	One 4-conductor Phoenix 12 AWG (3,3 mm ²)
Enclosure	MDF

Width	9.45" 240 mm
Height	11.02" 255 mm
Depth	6.10" 155 mm 6.10" 155 mm (with grille)
Weight	11.46 lbs 5.2 kg
Finish	Matte black and glossy white
Custom colour options	Piano lacquer: colour of choice, matt or other finishes upon request
Shape customization	Upon request
Mounting	Metal wall or ceiling mounting brackets that allows to angle the speaker further in two axes + 6 wall mount brackets, which allow to hang the speaker in multiple ways on the wall + VESA 100 x 100 mounting points

The THE6 PASSIVE WEDGE 30 is supplied with a front cover as standard

