

**THE DIRECTOR PRO**  
**ACTIVE EXT**  
**FLUSH**



Speaker type |  
Loudspeaker

Asymmetrical Waveguide Design with 8" AMT and a single or double 10" mid woofer | Asymmetrische Schallführung mit 200 mm AMT und einem oder zwei 254 mm Tiefmitteltöner

Passive | Active

Active, 2Ch DSP + 2Ch Amplifier are required | Aktiv, 2Ch DSP + 2Ch Verstärker werden benötigt

Recommended Amplifiers | Empfohlene Verstärker

low-mid 71 Vrms, 100 Vpk, 8,9 A; high 62 Vrms, 88 Vpk, 3,9 A; equivalent to LF 630W@8Ω, HF 240W@ 16Ω

Recommended ASCENDO Amplifiers

DNA 2250.2

Enclosure type | Prinzip

Vented | Reflex

Peak output | Spitzenleistung

127 dB peak / 1 x Director sub  
130 dB peak / 2 x Director sub  
105 dB peak / AMT Waveguide

Frequency Range | Frequenzbereich

78 Hz - 21 kHz / -3 dB

Woofer | Tieftöner

10" | 254 mm

Tweeter | Hochtöner

8" AMT

Speaker In Waveguide

Neutrik Speakon NI4

Speaker In Director Sub

Neutrik Speakon NL4

Enclosure | Gehäuse

Internally braced birch ply and MDF | Innenverstrebtes Birkensterrholz und MDF

Waveguide Width

17,25" | 438,8 mm

Waveguide Height

8,81" | 223,8 mm

Waveguide Depth

21,91" | 556,5 mm

Waveguide Weight

23,15 lbs | 10,5 kg

Director Sub Width

12,2" | 310 mm

Director Sub Height

12,6" | 320 mm

Director Sub Depth

13,39" | 340 mm

Director Sub Weight

18,74 lbs | 8,5 kg

Finish | Oberfläche

PU structural paint | Robuster Strukturlack schwarz

Mounting Waveguide | Montage Waveguide

2 x metal mounting brackets

Mounting Director Sub | Montage Director Sub

2 x metal mounting brackets

Technical modifications subject to change without further notice | Technische Änderungen vorbehalten

