



Report of THE10 PASSIVE ON WALL


ASCENDO

Date	Author	Changes	Version
15/06/2023	GL		V1
01/11/2023	GL		V2

Summary


1.	Pictures of measurements	3
2.	Frequency Response	4
3.	Impedance Curve.....	5
4.	Contour Plot	6
4.1.	Horizontal	6
4.2.	Vertical.....	7
5.	CEA2034 Spinorama	8
5.1.	Directivity Index.....	9
5.2.	In-Room response	10
5.3.	Early reflections	11
5.4.	Horizontal Reflections	12
5.5.	Vertical Reflections.....	13
5.6.	Horizontal Frequency Response.....	14
5.7.	Vertical Frequency Response	15
6.	Harmonic Distortion	16
7.	MTON Max SPL – 1s Stimulus.....	17
7.1.	Results	17
7.2.	Compression Chart	18
7.3.	Multi Tone Distortion Chart	19
8.	CEA2010B.....	20
8.1.	Max Peak SPL.....	20
8.2.	Max Peak Voltage	21
8.3.	THD on Burst.....	22

1. Pictures of measurements




2. Frequency Response

2,83v @1m – 1/6 oct. Smoothing




3. Impedance Curve

2,83v @1m – No Smoothing



4. Contour Plot

4.1. Horizontal



Referenced @10m – Baffle loaded (2π steradians)

Normalized on Axis – 1/6 oct. Smoothing

4.2. Vertical


Referenced @10m – Baffle loaded (2π steradians)



Normalized on Axis – 1/6 oct. Smoothing


5. CEA2034 Spinorama

2,83v @1m – 1/6 oct. Smoothing




5.1. Directivity Index

1/6 oct. Smoothing




5.2. In-Room response

1/6 oct. Smoothing




5.3. Early reflections

1/6 oct. Smoothing




5.4. Horizontal Reflections

1/6 oct. Smoothing




5.5. Vertical Reflections

1/6 oct. Smoothing




5.6. Horizontal Frequency Response

1/6 oct. Smoothing




5.7. Vertical Frequency Response

1/6 oct. Smoothing



6. Harmonic Distortion

1/6 oct. Smoothing – +7dBu Stimulus



7. MTON Max SPL – 1s Stimulus

7.1. Results

Results of last passed measurement


Parameter	Value	Unit	Description
$U_{\max}$	1.26	V	Root mean square of stimulus.
$SPL_{\max}$	118.99	dB	Sum level of fundamentals in microphone signal.
$C_{\max}$	2.92	dB	Max compression in the frequency range 80 - 19494 Hz.
$RMD_{\max}$	-25.43 (5.4)	dB (%)	Maximum multi-tone distortion of microphone signal relative to mean value.
TMDR	-20.46 (9.5)	dB (%)	Total multi-tone distortion ratio of microphone signal.

Stimulus properties

Parameter	Value	Unit	Description
$f_{\min}$	74.22	Hz	Lowest multi-tone frequency line
$f_{\max}$	21880.86	Hz	Highest multi-tone frequency line
t	0.51	s	Signal duration
K	2.95	-	Kurtosis
C	12.59	dB	Crest factor


7.2. Compression Chart

-32dB Voltage Values – 1/6 Smoothing




7.3. Multi Tone Distortion Chart

-32dB Voltage Values – No Smoothing




8. CEA2010B

8.1. Max Peak SPL



8.2. Max Peak Voltage

Maximum passed Input Voltage vs. Frequency Profile



8.3. THD on Burst

