TECHNICAL DATA
THE 15 Be PRO PASSIVE
ON WALL

ASCENDO
ELEVATE YOUR SOUND

Speaker Type	15" Beryllium dome, time-coherent point-source coaxial
Principle	Vented
Passive | Active	Passive
Woofer	15" woofer
Tweeter	3" voice coil diameter, Beryllium dome compression driver
Recommended ASCENDO Amplifiers	AIA2-2704, AIA2-6004, AIA4-2404, AIA4-6004, AIA8-6004
SPL (Peak / half space 2pi)	Measured Data 125 dB (Cont.) / 135 dB (Peak) 122 dB @ 60 Hz 112 dB @ 40 Hz
Frequency Range	Measured Data (Without DSP) 70 Hz - 21 kHz / -3dB
Efficiency	90 dB / 1 W/m 4 pi, 96 dB / 1 W/m 2 pi
Power Handling	900 W
Impedance	8 Ω
Directivity Horizontal x Vertical in deg°	85° x 85°
Input Terminal	Neutrik Speakon

Enclosure	Internally braced birch ply and MDF
Dimensions (W/H/D)mm (Without grille)	470 | 870 | 240 (With grille: 250.2)
Dimensions (W/H/D)inch (Without grille)	18 1/2 | 34 1/4 | 9 7/16 (With grille: 9 7/8)
Packing Dimensions (W/H/D)mm	340 | 970 | 550
Packing Dimensions (W/H/D)inch	13 6/16 | 38 3/16 | 21 10/16
Weight	78.26 lbs | 35.50 kg
Gross Weight	89.28 lbs | 40.50 kg
Finish	Structural paint black
Mounting	3 x wall brackets for horizontal and vertical installation, VESA 200 x 200 mounting option

The THE15 Be PRO PASSIVE ON WALL is supplied with a front cover as standard

Technical modifications subject to change without further notice | Technische Änderungen vorbehalten