



Speaker Type	6 1/2" time-coherent point-source coaxial
Principle	Vented
Passive   Active	Passive
Woofer	6 1/2" woofer
Tweeter	1" soft dome
Recommended ASCENDO Amplifiers	AIA2-1404, AIA4-2404, AIA8-2704, AIA8-6004
SPL (Peak / half space 2pi)	Measured Data 111 dB (Cont.) / 122 dB (Peak) 110 dB @ 100 Hz 117 dB @ 160Hz
Frequency Range	Measured Data (Without DSP) 95 Hz - 20 kHz / -3dB
Efficiency	87 dB / 1 W/m 4 pi, 93 dB / 1 W/m 2 pi
Power Handling	200 W
Impedance	8 Ω
Directivity Horizontal x Vertical in deg°	85° x 85°
Input Terminal	4-conductor Phoenix 12 AWG (3.3 mm <sup>2</sup> )

Enclosure	Internally braced MDF
Dimensions (W/H/D)mm (Without grille)	240   255   155 (Vertical) 240   155   255 (Horizontal)
Dimensions (W/H/D)inch (Without grille)	9 7/16   10 1/16   6 1/8 (Vertical) 9 7/16   6 1/8   10 1/16 (Horizontal)
Packing Dimensions (W/H/D)mm	370   370   280
Packing Dimensions (W/H/D)inch	14 9/16   14 9/16   11 1/16
Weight	11.46 lbs   5.2 kg
Gross Weight	14.33 lbs   6.5 kg
Finish	Matte black / White glossy
Mounting	Metal wall or ceiling mounting brackets allowing further angling in two axes, 6 x wall mount brackets for multiple hanging options, VESA 100 x 100 mounting points

The THE6 PASSIVE WEDGE 30 is supplied with a front cover as standard



Technical modifications subject to change without further notice | Technische Änderungen vorbehalten